


# 2024 KLX<sup>®</sup> 230 S

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



MSRP NON-ABS  
**\$4,999**

MSRP ABS  
**\$5,299**



## POWER

|                              |  |
|------------------------------|--|
| <b>Engine</b>                | 4-stroke single, SOHC, air-cooled        |
| <b>Displacement</b>          | 233cc                                    |
| <b>Bore x Stroke</b>         | 67.0 x 66.0mm                            |
| <b>Compression Ratio</b>     | 9.4:1                                    |
| <b>Maximum Torque</b>        | 13.2 lb-ft @ 6,400 rpm                   |
| <b>Fuel System</b>           | DFI <sup>®</sup> with 32mm throttle body |
| <b>Ignition</b>              | TCBI with Electronic Advance             |
| <b>Transmission</b>          | 6-speed                                  |
| <b>Final Drive</b>           | Sealed chain                             |
| <b>Electronic Rider Aids</b> | Anti-lock Brake System (ABS)             |

|                     |  |
|---------------------|--|
| <b>Rear Tire</b>    | 4.10 x 18  |
| <b>Front Brakes</b> | Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS) |
| <b>Rear Brakes</b>  | Single 220mm petal disc with single-piston caliper (and ABS)                   |

## PERFORMANCE

|  |   |
|--|---|
| <b>Front Suspension / Wheel Travel</b> | 37mm telescopic fork/7.8 in   |
| <b>Rear Suspension / Wheel Travel</b>  | Uni-Trak <sup>®</sup> linkage system and single shock with adjustable spring preload/8.7 in |
| <b>Front Tire</b>                      | 2.75 x 21   |

## DETAILS

|                         |  |
|-------------------------|--|
| <b>Frame Type</b>       | Perimeter, high-tensile steel  |
| <b>Rake/Trail</b>       | 24.6° /3.7 in  |
| <b>Overall Length</b>   | 81.8 in  |
| <b>Overall Width</b>    | 33.2 in  |
| <b>Overall Height</b>   | 44.8 in  |
| <b>Ground Clearance</b> | 9.4 in   |
| <b>Seat Height</b>      | 33.3 in  |
| <b>Curb Weight</b>      | 291.0/293.2 lb* 50-State Model   |
| <b>Fuel Capacity</b>    | 2.0 gal  |
| <b>Wheelbase</b>        | 53.7 in  |
| <b>Special Features</b> | ERGO-FIT <sup>®</sup> , LCD Instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE |
| <b>Color Choices</b>    | Lime Green, Battle Gray  |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.