## <sup>2024</sup> MULE PRO-MX<sup>™</sup> EPS







## POWER

| Engine                     | 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled                       |
|----------------------------|--|
| Displacement               | 695cc  |
| Maximum Torque             | 42.7 lb-ft @ 5,000 rpm   |
| Bore x Stroke              | 102.0 x 85.0mm   |
| <b>Compression Ratio</b>   | 10.3:1   |
| Fuel System                | DFI® with 44mm throttle body   |
| Transmission               | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)  |
| Final Drive                | Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock |
| Engine Braking             | Yes  |
| Alternator Output<br>(max) | 35.7 amp   |
|                            |  |

| r and brane type                | independent, meenanear bise                |
|---------------------------------|--|
| Ground Clearance                | 10.6 in                                    |
| Fuel Capacity                   | 9.5 gal                                    |
| Turning Radius                  | 14.0 ft                                    |
| Cargo Bed<br>Dimensions (LxWxH) | 33.4 x 44.1 x 9.1 in                       |
| Cargo Bed Load<br>Capacity      | 699 lb / 600 lb CA Model                   |
| Payload Capacity                | 1,200 lb                                   |
| Seating Capacity                | 2  |
| Towing Capacity                 | 1,500 lb                                   |
| Lighting                        | (2) Halogen headlights. (2) LED headlights |
|                                 |  |

Independent, Mechanical Disc

## **DETAILS**

Park Brake Type

## **Overall Length** 110.0 in **CAPABILITY Overall Width** 60.0 in **Overall Height** 74.4 in Front Suspension / Double wishbone/8.6 in Wheel Travel **Curb Weight** 1,587.6 lb\* / 1,589.8 lb\* CA Model **Rear Suspension /** Double wishbone/9.1 in Wheelbase 78.9 in Wheel Travel Instruments Multi-function display includes digital speedometer, **Front Tires** 25 x 8.00-12, radial fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning **Rear Tires** 25 x 10.00-12, radial indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt Steering Electric Power Steering (EPS), Tilt steering reminder lamps **Front Brakes** Dual Disc, 2 piston caliper Wheel Type Steel **Rear Brakes** Dual Disc, 1 piston caliper Timberline Green, Firecracker Red **Color Choices**

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE<sup>TM</sup> PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE<sup>TM</sup> side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

