# 2024 **NINJA® 650 KRT EDITION ABS**







## POWER

Engine	4-stroke, Parallel Twin, DOHC, 8-valve, liquid cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Fuel System	DFI® with dual 36mm Keihin throttle bodies
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), ABS

#### **Front Tire** 120/70 x 17 **Rear Tire** 160/60 x 17 **Front Brakes** Dual 300mm petal-type discs and 2-piston calipers and ABS Single 220mm petal-type disc and single-**Rear Brakes** piston caliper and ABS

### **DETAILS**

MSRP

DFI® with dual 36mm Keihin throttle bodies	Frame Type	Trellis, high-tensile steel
TCBI with Electronic Advance	Rake/Trail	24.0°/3.9 in
6-speed	Overall Length	80.9 in
Sealed chain	Overall Width	29.1 in
Kawasaki TRaction Control (KTRC), ABS	Overall Height	45.1 in
	Ground Clearance	5.1 in
	Clearance	
ANCE	Seat Height	31.1 in
41mm hydraulic telescopic fork/4.9 in	Curb Weight	423.4 lb*
	Fuel Capacity	4.0 gal
Horizontal back-link with adjustable spring	Wheelbase	55.5 in
preload/5.1 in	Color Choices	Lime Green/Ebony

## PERFORMANCE

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

```
Horizontal back-link with adjustable
preload/5.1 in
```

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.