## 2024 **RIDGE<sup>®</sup> XR HVAC**







12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,499/1,100 lb CA Model

Ladder type, tubular steel

1,960.3/1,962.5 lb\*\* CA Model

2, bucket seat

All-LED lighting

2,500 lbs

125.4 in

64.0 in

82.3 in

13.8/14.6 in (max preload); 13.8 in CA Model

**Ground Clearance** 

**Fuel Capacity** 

**Turning Radius** 

(LxWxH) **Cargo Bed Load** 

Capacity **Payload Capacity** 

Lighting

Frame

**Seating Capacity** 

**Towing Capacity** 

DETAILS

**Overall Length** 

**Overall Width** 

**Overall Height** 

**Dry Weight** 

**Cargo Bed Dimensions** 

## **POWER**

Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled	
Displacement	999cc	
Maximum Horsepower	116.0 hp <sup>1</sup> @ 8,500 rpm	
Maximum Torque	73.8 lb-ft @ 8,000 rpm	
Bore x Stroke	73.4 x 59.0mm	
Compression Ratio	10.6:1	
Fuel System	EFI	
Ignition	TCBI with Digital Advance	
Starting System	Electric	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	
Final Drive	Selectable 4WD with locking front/rear differential, shaft	
Engine Braking	Yes	
Alternator Output (max)	85 amp	
Electronic Rider Aids	Power Modes, Economical Riding Indicator	

## **CAPABILITY**

CAPABILITY		Curb Weight	2,066.1/2,068.3 lb* CA Model
Front Suspension /	Long-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in
Wheel Travel Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical
Front Tires	Duro 30 x 10-14		Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking
Rear Tires	Duro 30 x 10-14		indicator, oil pressure, water temperature)
Wheel Type	14" Aluminum	Additional Features	Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	Ice Gray, Metallic Graystone





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.