Z500 SE ABS





MSRP \$6,299



CANDY PERSIMMON RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE GRAPHENESTEEL GRAY



POWER

4-stroke, Parallel Twin, DOHC, liquid-cooled **Engine**

51.0 hp¹ @ 10,000 rpm

31.7 lb-ft @ 7,500 rpm

Displacement 451cc

70.0 x 58.6mm

11.3:1

Bore x Stroke Compression

Ratio

Maximum

Horsepower

Maximum Torque

Fuel System

Ignition TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider Aids

Economical Riding Indicator, Anti-lock Brake

System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

DFI® with dual 32mm throttle bodies

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable spring

preload/5.1 in

110/70-17

Rear Tire 150/60-17

Front Brakes Single 310mm semi-floating disc with 2-piston

calipers and ABS

Rear Brakes Single 220mm disc with single-piston caliper and

DETAILS

Trellis, high-tensile steel **Frame Type**

24.5° / 3.6 in Rake/Trail

Overall Length 78.5 in

Overall Width 31.5 in

Overall Height 43.3 in

Ground Clearance 5.7 in

30.9 in **Seat Height**

Dry Weight 339.6 lb** / 341.8 lb** 50-State Model

Curb Weight 370.4 lb* / 372.6 lb* 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features ERGO-FIT®, Full-color TFT Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE APP,

USB-C outlet

Color Choices Candy Persimmon Red/Metallic Flat Spark Black/

Metallic Matte Graphenesteel Gray

Scan with camera to view videos, key features and more.

Front Tire



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.