2025 MULE PRO-FX[™] 1000 HD EDITION







POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas
Displacement	999cc
Maximum Torque	61.5 lb-ft @ 4,500 rpm
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	10.1:1
Fuel System	DFI® with 38mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	90 amp

Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Cargo Bed Load Capacity	999/600 lb CA Model
Payload Capacity	1,616.3/1,263.5 lb CA Model
Seating Capacity	3
Towing Capacity	2,000 lb
Lighting	(2) Halogen headlights, (2) LED headlights

136.6 in

64.0 in

11.9 in (max), 11.8 in (std)

DETAILS

Overall Length

Overall Width

Ground Clearance

CAPABILITY

UAF ADILITT				
			Overall Height	81.1 in
	Front Suspension / Wheel Travel	Double wishbone/11.0 in	Dry Weight	1,816.9/1,819.1 lb** CA Model
	Rear Suspension /	Double wishbone/10.1 in	Curb Weight	1,891.9/1,894.1 lb* CA Model
W	Wheel Travel		Wheelbase	92.3 in
	Front Tires	26 x 9-12, radial	Instruments	Multi-function display includes digital speedometer, fuel
	Rear Tires	26 x 11-12, radial		gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator,
	Wheel Type	Steel		oil pressure warning indicator, fuel injection warning
	Steering	Rack-and-pinion		indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
	Front Brakes	Dual disc, 2-piston caliper	Additional Features	Roof, Rear Bumper, Additional Under Seat Storage Bin,
	Rear Brakes	Dual disc, 1-piston caliper		Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear Suspension, Anti-cinch Seatbelts
	Park Brake Type	Independent, mechanical disc	Color Choices	Firecracker Red

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.