## 2025 NINJA H2<sup>®</sup> CARBON ABS





MSRP **\$36,200** 



MIRROR COATED MATTE SPARK BLACK/ CANDY FLAT BLAZED GREEN



Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback

reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and top-

## POWER

PERFORMANCE

Front Suspension /

Wheel Travel

Scan with camera

to view videos,

key features

and more.

Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
<b>Compression Ratio</b>	8.5:1
Maximum Horsepower	239.6 hp <sup>1</sup> @ 11,500 rpm
Maximum Torque	104.9 lb-ft @ 11,000 rpm
Fuel System	DFI® with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger
Ignition	TCBI with Digital Advance
Transmission	6-speed, return shift, dog-ring
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper

top-out springs/4.7 in

43mm inverted Kayaba AOS-II fork with adjustable rebound

and compression damping, spring preload adjustability and

## Front Brakes Dual 330mm semi-floating discs with dual radial-mount, opposed 4-piston Brembo Stylema® calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) Rear Brakes Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

outspring/5.3 in

120/70-17 200/55-17

## DETAILS

Rear Suspension /

Wheel Travel

**Front Tire** 

**Rear Tire** 

Frame TypeTrellis, high-tensile steel, with swingarm mounting plateRake/Trail24.5°/4.1 inOverall Length82.1 in
Overall Length 82.1 in
Overall Width 30.3 in
Overall Height 44.3 in
Ground Clearance 5.1 in
Seat Height 32.5 in
Dry Weight 480.7 lb**
Curb Weight 524.8 lb*
Fuel Capacity 4.5 gal
Wheelbase 57.3 in
Special Features Supercharged engine, All-digital TFT color Instrumentation, All-LED lighting, Carbon fiber, Highly Durable Paint, Serial number stamp, Smartphone Connectivity via RIDEOLOGY THE APP
Color Choices Mirror Coated Matte Spark Black/Candy Flat Blazed Green

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.