

2025

NINJA® ZX™ -14R ABS

Kawasaki
Let the Good Times Roll®



MSRP
\$17,599



METALLIC MATTE SOVEREIGN RED/METALLIC FLAT SPARK BLACK/
METALLIC MATTE GRAPHITE GRAY



POWER

Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	1,441cc
Bore x Stroke	84.0 x 65.0mm
Compression Ratio	12.3:1
Maximum Horsepower	197.0 hp ¹ @ 10,000 rpm
Maximum Torque	116.5 lb-ft @ 7,500 rpm
Fuel System	DFI® with 44mm Mikuni throttle bodies (4)
Ignition	TCBI with Electronic Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock Brake System (ABS)

Rear Suspension / Wheel Travel	Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in
Front Tire	120/70-17
Rear Tire	190/50-R17
Front Brakes	Dual 310mm semi-floating Brembo discs with dual radial-mounted Brembo 4-piston M50 monobloc calipers and ABS
Rear Brakes	Single 250mm disc with twin-piston caliper and ABS

DETAILS

Frame Type	Aluminum monocoque
Rake/Trail	23.0° / 3.7 in
Overall Length	85.4 in
Overall Width	30.3 in
Overall Height	46.1 in
Ground Clearance	4.9 in
Seat Height	31.5 in
Curb Weight	593.1 lb*
Fuel Capacity	5.8 gal
Wheelbase	58.3 in
Color Choices	Metallic Matte Sovereign Red/Metallic Flat Spark Black/Metallic Matte Graphite Gray

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in
---------------------------------	-----------------------------------------------------------------------------------------------------------------------

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.