ALL-NEW 2025

RIDGE® XR CREW LIMITED HVAC





\$38,099



METALLIC BLUISH GRAY



POWER

4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled **Engine**

999cc **Displacement**

Maximum Horsepower 116.0 hp1 @ 8,500 rpm **Maximum Torque** 73.8 lb-ft @ 8,000 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1 EFI

Fuel System

Ignition TCBI with Digital Advance

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R) **Final Drive** Selectable 4WD with locking front/rear differential, shaft

Engine Braking Yes

Alternator Output (max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator

Fuel Capacity Turning Radius

Cargo Bed Dimensions

(LxWxH)

Ground Clearance

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

13.4/14.6 in (max preload); 13.4 in CA Model

12.9 gal

19.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1.290/1.076 lb CA Model

5-person (2 row), bench seats

2,500 lb

All-LED lighting

DETAILS

Frame Ladder type, tubular steel

Overall Length 161.1 in **Overall Width** 64.0 in **Overall Height** 82 3 in

2,513.7/2,515.9 lb** CA Model **Dry Weight Curb Weight** 2,624.0/2,626.2 lb* CA Model

Wheelbase

Instruments Digital speedometer, tachometer, fuel gauge, odometer, dual

trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil

pressure, water temperature)

Additional Features

8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Fullcolor TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible

Color Choices Metallic Bluish Gray

CAPABILITY

Front Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Rear Suspension / **Wheel Travel**

Wheel Type

Steering

Long-Travel, Double Wishbone/12.7 in

Duro 30 x 10-14 **Front Tires Rear Tires** Duro 30 x 10-14

Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes Dual hydraulic 249mm discs with two-piston calipers

14" Aluminum

Rear Brakes Dual hydraulic 249mm discs with single-piston calipers

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.