TERYX KRX® 1000 BLACKOUT EDITION





\$24,999



Cargo Bed Dimensions

(LxWxH)

Capacity

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

FLAT EBONY



14.6 x 33.1 x 9.1 in

351 lh

781 lb

2

N/A

POWER

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine**

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

TCBI with electronic advance Ignition

Starting System

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive**

Engine Braking

DETAILS

Lighting

Frame Ladder type, tubular steel

Overall Length 133.3 in **Overall Width** 68.1 in **Overall Height** 76.0 in

Curb Weight 2,030.8 lb* / 2,033.0 lb* CA Model

Wheelbase 98.8 in

Instruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge,

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

(2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light

lamp, and CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

Additional Features LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper,

Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch

Color Choices Flat Ebony

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel

Steering

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.0 in (max), 13.4 in (std)

Fuel Capacity 10.6 gal **Turning Radius** 20.3 ft

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.