## **ALL-NEW 2025 W230 ABS**









METALLIC OCEAN BLUE/EBONY

POWER		Front Tire Rear Tire	90/90-18 110/90-17	
Engine	4-stroke, single-cylinder, SOHC, 2 valves, air- cooled	Front Brakes	Single 265mm disc with 2-piston calipers, ABS	
Displacement	233cc	Rear Brakes	Single 220mm disc with 1-piston caliper, ABS	
Bore x Stroke	67.0 x 66.0mm	DETAILS		
Compression Ratio	9.0:1	Frame Type	Semi-double cradle, steel	
Maximum Torque	14.0 lb-ft @ 5,800 rpm	Rake/Trail	27.0°/3.7 in	
Fuel System	DFI® with 32mm throttle bodies	Overall Length	83.6 in	
Ignition	TCBI with Digital Advance	Overall Width	31.4 in	
Transmission	6-speed, return shift	Overall Height	42.9 in	
Final Drive	Sealed chain	Ground Clearance	5.9 in	
Electronic Rider Aids	Anti-lock Brake System	Seat Height	29.3 in	
DEDEODMANOE		Dry Weight	293.2 lb**	

## PERFURMANCE

Front Suspension / Wheel Travel	37mm tetes
Rear Suspension	Twin shocks

37mm telescopic fork/4.6 in

/ Wheel Travel

s with spring preload adjustability/3.7 in

315.2 lb\*

3.1 gal

55.7 in

Metallic Ocean Blue/Ebony

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Curb Weight** 

**Fuel Capacity** 

**Color Choices** 

Wheelbase

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.