



# NEW 2025 Z900 ABS

**Kawasaki**  
Let the Good Times Roll®



MSRP  
**\$9,999 - \$10,299**

-  METALLIC SPARK BLACK/METALLIC CARBON GRAY/EBONY
-  GALAXY SILVER/METALLIC SPARK BLACK/PHANTOM BLUE



## POWER

<b>Engine</b>	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
<b>Displacement</b>	948cc
<b>Bore x Stroke</b>	73.4 x 56.0mm
<b>Compression Ratio</b>	11.8:1
<b>Maximum Horsepower</b>	123.0 hp <sup>1</sup> @ 9,500 rpm
<b>Maximum Torque</b>	73.1 lb-ft @ 7,700 rpm
<b>Fuel System</b>	DFI® with 36mm throttle bodies
<b>Ignition</b>	TCBI with Electronic Advance
<b>Transmission</b>	6-speed, return shift
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

<b>Front Tire</b>	120/70-17
<b>Rear Tire</b>	180/55-17
<b>Front Brakes</b>	Dual 300mm semi-floating discs with radial-mount 4-piston calipers and ABS
<b>Rear Brakes</b>	Single 250mm disc with single-piston caliper and ABS

## DETAILS

<b>Frame Type</b>	Trellis, high tensile steel
<b>Rake/Trail</b>	24.7°/4.3 in
<b>Overall Length</b>	81.3 in
<b>Overall Width</b>	32.7 in
<b>Overall Height</b>	43.3 in
<b>Ground Clearance</b>	5.7 in
<b>Seat Height</b>	31.9 in
<b>Dry Weight</b>	423.4 lb** / 425.6 lb** 50-State Model
<b>Curb Weight</b>	467.5 lb* / 469.7 lb* 50-State Model
<b>Fuel Capacity</b>	4.5 gal
<b>Wheelbase</b>	57.1 in
<b>Special Features</b>	5" All-digital TFT color instrumentation, All-LED lighting, ERGO-FIT®, Smartphone Connectivity with Voice Command and Turn-by-Turn Navigation via RIDEOLGY THE APP MOTORCYCLE
<b>Color Choices</b>	Metallic Spark Black/Metallic Carbon Gray/Ebony, Galaxy Silver/Metallic Spark Black/Phantom Blue

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	41mm inverted telescopic fork with rebound damping and spring preload adjustability/4.7 in
<b>Rear Suspension / Wheel Travel</b>	Horizontal back-link, gas-charged rear shock with rebound damping and spring preload adjustability/5.5 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). Specifications subject to change.

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.